

## Hand-Setting Tool Type SGT

### Product Description

- Manually operated setting tool to install fischer FZP undercut anchors FZP-II-T for thin panel materials

### Advantages

- Easy and safe to handle
- Compact design
- Manual pressure point for smooth setting even in critical materials

### Technical Details (range of delivery)

- Delivery includes plastic carrying case
- On demand additional parts are available for setting Internal Thread Anchor M6 (FZP-II-i)
- Suitable for FZP-II-T Anchors with bolt projection length 9 to 16mm

### Operation Steps

1. Insert FZP-T Anchor through the nosepiece and screw it into the mandrel inside.
2. Put FZP-T Anchor into the undercut hole
3. Hold the tool vertical to panel surface and press it downwards with little force in direction anchor-drill hole axis.
4. Whilst keeping downwards force constant, press action levers repeatedly together until plastic washer of FZP-T Anchor is flush mounted onto panel surface.
5. Press the action lever to the front until a clicking-noise can be heard clearly.
6. Unscrew the FZP-T Anchor threaded stud from the tool by turning the knurled-head bolt at the head of tool.



### Technical Details

Dimensions (Plastic carrying case)	36 x 31 x 6 cm (B x T x H)
Total weight (including second battery)	1.5 kg
<b>Setting Tool</b>	
Weight (Setting tool)	Ca. 800 gr
Total stroke	Ca. 5 mm
Costs / Configuration	For purchase refer to separate list

### ACT Service

fischerwerke GmbH & Co. KG

Werk Altheim · Hindenburgstr. 81 · D-72160 Horb

Phone +49 (0)74 43 12-45 53 · Fax +49 (0)74 43 12-49 07

act@fischer.de · www.fischer.de